

Augmenting Multi-Touch with Commodity Devices

Francisco R. Ortega
Florida International University
10555 W. Flagler St., EC-3981
Miami, FL., 33174
+1 (305) 348-6072
forte007@fiu.edu

Armando Barreto
Florida International University
10555 W. Flagler St., EC-3981
Miami, FL., 33174
+1 (305) 348-3711
barretoa@fiu.edu

Naphtali Rishe
Florida International University
11200 SW 8th St, ECS-243
Miami, FL., 33199
+1 (305) 348-1706
ndr@acm.org

ABSTRACT

We describe two approaches to augment multi-touch user input with commodity devices (Kinect and wiiMote).

Categories and Subject Descriptors

D.2.2 [Design Tools and Techniques]: User Interface Interactions.

General Terms

Algorithms, Design, Human Factors.

Keywords

Multi-touch; 3D User Interfaces; Human-Computer Interaction.

1. INTRODUCTION

Seeking the development of efficient 3D user interfaces, we proposed augmenting multi-touch displays for 3D navigation with our current work in progress. Multi-touch interaction for 3D environments has been explored before for domain specific [1]. There have been many attempts to augment the multi-touch displays. For example, Z-Touch [5] captures a depth map to add the z-axis to the touch display. The Z-Touch has limitations and it is not a commodity device. Augmenting the touch with a force sensor has also been tried [3]. Our approach involves commodity devices to augment multi-touch. Other previous works have used mice and keyboard in surface displays and XBOX Kinect to augment touch [2,4].

2. PROPOSED APPROACH

We are using a desktop 3M Multi-Touch 22" display, Microsoft Windows Kinect, and wiiMote with MotionPlus. We used the touch data, the Kinect depth stream, the wiiMote and Motion Plus accelerometer data (a_x , a_y , a_z) and the gyroscope data (roll and pitch only), as shown in Figure 1.

Our first attempt was to use the Kinect. The problem with the Kinect[6] is that when the user is close to the display, the depth stream becomes part of the background. We believe that using the Intel Perceptual Computing camera will yield better results. Our

second approach was to use the wiiMote with the Motion Plus to get extra sensory devices for the z-axis. While we know that the wiiMote is not ideal to combine with touch, the test allowed us to set us into the direction of augmenting with 9-axis Micro-Electro-Mechanical Systems (MEMS) attached to one or two hands in form of a watch. We can see that augmenting the touch with MEMS will yield a better interaction.



Figure 1. 3D Navigation Setup.

3. CONCLUSION

While it may be possible to find intuitive gestures for multi-touch displays, is the fusion of devices that may give a complete Natural User Interaction (NUIs).¹

4. REFERENCES

- [1] Chi-Wing, F., Wooi-Boon G., and Junxiang Ng, A. 2010 "Multi-touch techniques for exploring large-scale 3D astrophysical simulations," Proceedings of the 28th international conference on Human factors in computing systems.
- [2] Hartmann B, Morris, M. R., Benko, H., and Wilson, A. D. 2009. "Augmenting interactive tables with mice & keyboards," presented at the the 22nd annual ACM symposium, New York, New York, USA. p. 149.
- [3] Heo, S. and Lee, G. 2011. "Force gestures: augmenting touch screen gestures with normal and tangential forces," pp. 621–626.
- [4] Lai, H. 2011. "Using Commodity Visual Gesture Recognition Technology to Replace or to Augment Touch Interfaces," presented at the 15th Twente Student Conference on IT.
- [5] Takeoka, Y., Miyaki, T., and Rekimoto, J. 2010. "Z-touch: an infrastructure for 3d gesture interaction in the proximity of tabletop surfaces," pp. 91–94.

¹ This work was sponsored by NSF grants HRD-0833093, CNS-0959985, and GAANN fellowship.